



ELECTRIC STACKER WITH WRAP-OVER FORKS

Extremely robust and well engineered range of heavy duty all electric stackers with narrow wheel arms and wrap-over forks. Two stage mast (except CLC1214H which is single mast) for maximum lowered height flexibility. The stacker is a pedestrian walkie type but also fitted with a hinged ride-on stand plate.

- Electromagnetic brake system.
- Curtis control unit.
- Polyurethane drive and bearing wheels.
- Load centre 600mm.
- Lift pump motor 3kw (2kw on 1200kg models).
- Battery voltage/cap ah: 24/280 (2 x 12/100 on 1200kg models).
- Service weight with battery: 1240kg (500/570/630 respectively on 1200kg models).
- Standard fork length: 1150mm (1220mm option available).



REF	Lifting cap kg	Lift height mm	Overall L x W mm	Extended height mm	Lowered height mm	Turning radius mm	Travel speed laden/unladen	PRICE
CLC1214H	1200	1400	1755	2014	2014	1366	4/4.2	£4931.36
CLC1225H		2500	795	2924	1724			£5363.52
CLC1233H		3300	2050	3924	2185			£6156.80
CLC1614H	1600	1400	x	1900	1185	1580	5/5	£10078.80
CLC1625H		2500	856	3000	1765			£10286.00
CLC1633H		3300	2050	3800	2135			£10804.00
CLC2014H	2000	1400	x	1900	1185	1580	5/5	£13160.16
CLC2025H		2500	856	3000	1765			£13317.04
CLC2033H		3300		3800	2135			£13645.60



Our expert says

Fully electric stacker training individual or groups
REF: ACTRAIN/FES from £147.25

ELECTRIC STACKERS WITH STRADDLE WHEEL ARMS

Extremely robust and well engineered range of heavy duty all electric stackers with wide straddle wheel arms to suit pallets with perimeter base boards. Two stage mast for maximum lowered height flexibility. The stacker is a pedestrian walkie type but also fitted with a hinged ride-on stand plate.

- Electromagnetic brake system.
- Curtis control unit.
- Polyurethane drive and bearing wheels.
- Load centre 600mm.
- Lift pump motor 3kw.
- Battery voltage/cap ah: 24/280.
- Service weight with battery: 1370kg (580/650/656 respectively on 1200kg models).
- Standard fork width: 1070mm.



REF	Lifting cap kg	Lift height mm	Overall L x W mm	Extended height mm	Lowered height mm	Turning radius mm	Travel speed laden/unladen	PRICE
CLC1214HS	1200	1400	2005 x 1470	1900	1135	1565	5/5	£5766.08
CLC1225HS		2500		3000	1765			£6221.92
CLC1233HS		3300		3800	2135			£6427.64
CLC1614HS	1600	1400		1900	1185			£10614.56
CLC1625HS		2500		3000	1765			£10952.00
CLC1633HS		3300		3800	2135			£11369.36
CLC2014HS	2000	1400		1900	1185			£13734.40
CLC2025HS		2500		3000	1765			£14023.00
CLC2033HS		3300		3800	2135			£14267.20