

TAPER GRIP DRUM CLAMP ATTACHMENT

- CE marked and plated.
- Suitable for use on 210 litre steel drums.
- The steel jaws grip the rim of the drum, allowing the drums to be picked up or set down without spaces between them.
- Automatic grip lock will not open and ensures safe drum transportation.
- Grip head has different positions to fit different heights.
- Capacity: single 360kg, double 720kg.

REF	No of drums held	Fork spread	Overall size L x W x H mm	Weight kg	PRICE
DLC01Z	1	560mm	830 x 710 x 1000	60	£753.71
DLC02Z	2	605mm	1030 x 850 x 1000	96	£933.73



NB It is important for the safe use of this unit that the drum ring is not damaged and is strong enough to support its own weight.



HEAVY DUTY RIM GRIP DRUM HANDLER ATTACHMENT

The drum handler to choose for handling drums packed tightly together. Steel jaws grip the rim (chimb) of the drum, allowing the drums to be picked up or set down without spaces between them. Ideal for stuffing and destuffing containers and suitable for use on rough terrain. May be used with 120 or 210 litre drums of steel, 'L' ring or 'XL' ring plastic types. A rubber lined clutch support cushions drums during transport. This model is available with a mild steel frame and a zinc plated head as standard, which is suitable for most applications.

REF	Max SWL kg	Size mm	Spread mm	Load centre	C of G	No of drums	Drum types	PRICE
PB-1	750	140 x 50	560	187	570	1	Steel & L ring	£871.35
PB-2	1500	140 x 50	560	187	640	2	plastic	£1326.45

CRANE SLUNG DRUM ROTATOR ATTACHMENT

Rotation is carried out by means of a crank handle (for below shoulder operation), a continuous loop chain (for operation above shoulder height) or by hydraulic motor to replace the handle/chain that is connected to the aux valve on the truck. Supplied without hoses. Fitted with a heavy duty gearbox for precise and controlled pouring.

Designed primarily for sitting under an overload crane for decanting the contents of 210 litre steel drums or 210 litre 'L' and 'XL' plastic drums. Drums are retained in the attachment by two webbing harnesses and ratchets to avoid slippage.



DTR-3-DS

REF	Max SWL kg	Max fork size mm	Method of operation	Drum types	Weight kg	PRICE
DTR-3-DS	360	140 x 50	Crank handle	Steel & L ring	92	£1637.25
DTR-4-DS	360	140 x 50	Loop chain	plastic	94	£1792.65
DTR-3-DSH	360	140 x 50	Hydraulic		113	£4351.20



Our expert says

Have precise control over pouring



DRUM TILTING AND DISPENSING FORK ATTACHMENT

- Two models available looped hand chain for controlled geared tilting at high level or lever handle for low level.
- Suitable for 210 litre open top or tight head drums with rolling hoops.
- Complete with fork sleeves to take maximum 150 x 60mm at 820mm centres of fork pockets. Thumb screw locations for fork sleeve safety.
- Capacity rating at 500mm load centres. Fully tested 33% live overload.
- Manufactured to health and safety standard.
- Quick, easy to fit girdle. Standard height high level 3m.
- Finish: Standard blue.

REF	Type	SWL	Weight kg	PRICE
PFDT3LL	High level	360kg	88	£1542.40
PFDT3H	Low level	360kg	88	£1518.40