

LOADING DOCK EQUIPMENT

COLLAPSIBLE DOCK SHELTER

- This product of ingenuity is low cost and low maintenance. It compensates for a wide variety of vehicle sizes and poorly aligned vehicles, by collapsing if hit in a particular way, resulting in minimal damage.
- Manufactured from polyester Trevira fabric with PVC UV resistant coating on both sides ensuring very high tear resistance. Up to 900mm projection possible (standard projection 600mm).
- Reduces weather ingress, minimising slip hazards and lessening harm to goods due to water damage.



REF	Usable width mm	Usable min height mm	Usable max height mm	PRICE
TCDS403016	2300 - 2800	Dock height + 2500	Dock height + 3000	POA
TCDS2415	Optional corner sealing pad, 2 required per shelter			POA

new



DELUXE DOCK LIGHT

The installation of a dock light provides additional safety and convenience to operatives.

- Steel construction with a hinged bracket, pivoted at 3 points.
- The unit has an IP565 rating suitable for both indoor and outdoor.
- Arm length is 11000mm extended.
- Built-in single pole switch.
- 30w LED Lamp.
- 3,300 lumens output.
- Supply voltage: 110-240v input.
- Weight: 6.5kg.



REF	PRICE
TWDL-5L	£404.55



WHEEL GUIDES/ALIGNMENT CURBS

- Invaluable safety and efficiency aid for guiding lorries into the correct position.
- We recommend guides are fitted below ground by casting into concrete for added strength. Alternatively, guides can be fitted above ground by bolting to concrete.



- Available as either straight section or flared to guide vehicles into loading areas.
- Painted in alert yellow.

REF	Config	Fixing type - above/below ground level	Wt kg	Dimensions mm		PRICE
				Above ground	O/A length	
TWAC-18-A-B	Straight	Above	57	320	1800	£545.49
TWAC-18-B-B	Straight	Below	64	320	1800	£514.50
TWAC-28-A-F	Splayed	Above	77	320	2800	£613.68
TWAC-28-B-F	Splayed	Below	75	320	2800	£657.07