MODULAR LOADING DOCKS

The absence of a raised loading dock can be a threat to safety and also uneconomic. This can be remedied with our versatile modular system which can be designed to suit individual locations and requirements.

- Its semi-permanent nature allows quick simple relocation or change of layout.
- Rugged construction for up to eight tons axle load.
- · Minimum disruption during installation.
- · Smart streamline appearance.
- · Complies with Health and Safety Regulations.
- · A wide range of accessories are available.
- Dock is a valuable asset to the company.
- Contact us now for a free survey and quotation.
 We offer a full supply, delivery
- and installation service.
- · Platforms can be provided in heights ranging from 800 to 1,600mm.



REF	Description	L x W x H m	Weight kg	PRICE
TMD-SM	Standard Module	3.57 x 2.38 x 1.0	1110	POA
TMD-DL	Dock Leveller Module	3.57 x 2.38 x 1.0	600	POA
TMD-FTR	Fork Truck Rave	0.3 high	24/m	POA
TMD-PTR	Pallet Truck Rave	0.04 high	5/m	POA
TMD-HR	Hand Rail	1.00 high	19/m	POA
TMD-AS	Access Steps	0.81 wide	115	POA
TMD-CL	Cat Ladder	0.81 wide	66	POA





LIGHTWEIGHT MOBILE PLATFORMS

We are able to supply platforms to suit any loading/unloading or assembly applications. These platforms are bespoke made to suit your requirements so please contact our sales department for further details and prices.

- · Designed with a 2,000kg SWL for lightweight (un)loading applications.
- Suitable for use with pallet trucks, sack trucks or hand balling of goods for fast, safe loading and unloading of your vehicles.
- Fitted with fork truck pockets to the sides for quick and easy positioning.
 Hinged barriers with gas springs for lightweight operation, a heavy duty shootbolt to lock in both the raised and lowered position, 20mm high pallet raves and 100mm D-Section bumpers.
- · Height adjustable legs in 50mm increments 1100 1550mm.
- · Access ladders with a twin hinged barrier to the opening, handrails and rubber bumpers fitted as standard.
- Optional locking swivel castors.
 Options bridging the gap between platform and vehicle: Removable Dockplate.

Sliding Hinged Bridgeplate.

Heavy Duty Piano Hinged Bridgeplate.

- Chain hooks and tensioning brackets to connect the platform to the vehicle where possible.
- Standard sizes 2.4 x 2.5m or 2.4 x 3.6m (non standards available on request).



