

ANTI-SLIP TAPES

DIAMOND GRIP ANTI-SLIP TAPE

A comprehensive range of anti-slip surfacing products designed to promote floor level safety in the workplace. Suitable for light and heavy foot traffic and available in a choice of finishes - general purpose, coarse or aquasafe.

General Purpose:

- Self-adhesive anti-slip tape for general use around factories, stairs, ramps etc.
- Water, oil and chemical resistant.

Coarse:

- Tough, diamond hard material for heavy duty use ideal for heavy plant and construction equipment.
- Resistant to clogging.

Aquasafe:

For barefoot comfort and safety in wet areas.
Textured vinyl top surface and moisture resistant backing.







REF	Туре	Size W x L	PRICE
DG/25	Roll	25mm x 18.3m	£23.56
DG/50	Roll	50mm x 18.3m	£40.23
DG/100	Roll	100mm x 18.3m	£73.55
00/100	Tton	Tooliilii x To.olii	~10100



HAZARD ANTI-SLIP TAPE

- General purpose grade anti-slip tape with hazard chevrons for added safety.
- Comes in black/yellow.
 Size:
- 18.3m roll x 50mm wide.





Size W x L mm	Colour	PRICE
810 x 1220	Yellow	£87.21
810 x 1220	Black	£87.21
1220 x 1220	Yellow	£132.38
1220 x 1220	Black	£132.38
1220 x 2440	Yellow	£262.73
1220 x 2440	Black	£262.73
	810 x 1220 810 x 1220 1220 x 1220 1220 x 1220 1220 x 1220 1220 x 2440	810 x 1220 Yellow 810 x 1220 Black 1220 x 1220 Yellow 1220 x 1220 Black 1220 x 2440 Yellow

ANTI-SLIP FLAT SHEET

Suitable for indoor and outdoor use, in all conditions these sheets are ideal for marking out walkways, giving clear routes of access with strong anti-slip properties.



- Provides an immediate improvement in safety in
- any environment. • Water, oil and chemical
- resistant. • Service temperature: -50°C to 110°C.
- 4mm thick.
- Text and symbols can be formed in the grit surface at an extra cost.



- Robust fibreglass GRP construction designed to withstand the harshest of conditions.
- Impregnated fire-resistant additive ensure excellent fire and heat resistance, conforming to ASTM E84
- Suitable for indoor and outdoor use, in all conditions.
- Service temperature: -50°C to 110°C.
- 4mm thick.
- Available in black/yellow, black, yellow or white.

NOSING COVERS

These can be applied to any existing concrete, metal or wood steps where frequent use or exposure to slippery conditions increases the risk of accidents. They also improve the appearance of aged or damaged steps where it is important to maintain a pleasing aesthetic as well as a safe environment.

^{nt} ☆ **Ł 62, 62, 62**

REF Size mm		Length mm	PRICE
SN0216	55 x 55	400	£13.96
SN0220	55 x 55	500	£15.68
SN0224	55 x 55	600	£17.40
SN0230	55 x 55	750	£19.97
SN0239	55 x 55	1000	£24.25
SN0259	55 x 55	1500	£32.84
SN0210	55 x 55	3000	£58.59

GP STAIR TREAD

These stair treads can be applied to any existing concrete, metal or wood steps where frequent use or exposure to slippery could increase the risk of accidents. They also help to improve the appearance of aged or damaged steps.

- Robust fibreglass GRP construction designed to withstand the harshest of conditions.
- Impregnated fire-resistant additive ensure excellent fire and heat resistance, conforming to ASTM E84.
- Suitable for indoor and outdoor use, in all conditions.
- Service temperature: -50°C to 110°C.
- 4mm thick.
- Available in black/yellow, black or yellow.



